

Aluminium Narrow Span Scaffolding Series

- Lightweight Aluminium Scaffolding
- Fastest erection & dismantling compared to other scaffolding
- Full handrails on all towers
- Stabilizers supplied for all towers above 4.5m
- Lockable, height-adjustable castors on all towers
- Trap-door access platforms on all towers
- Safety harness available
- Bridging platforms up to 7.2m available
- Tower dimension 1.8m x 0.9m
- Platform heights from 2.2m up to 8.2m with stabilizers
- Max height 8.2m tied to the structure

Specs	2.2m	3.2m	4.2m	5.2m	6.2m	7.2m	8.2m
Four Rung Frame	2	2	4	4	6	6	8
Two Rung Frame	0	2	0	2	0	2	0
Guard Rail Frame	2	2	2	2	2	2	2
Horizontal Braces (yellow hooks)	6	6	6	6	6	6	6
Diagonal Braces (red hook)	4	6	8	10	12	14	16
Trapdoor Platform	1	1	2	2	3	3	4
Triangular Stabiliser	0	4 (M)	4 (M)	4 (M)	4 (L)	4 (L)	4 (J)
Adjustable Castors (200mm)	4	4	4	4	4	4	4
Lock Braces	L2	L4	L4	L6	L6	L8	L8
Toe Board Sets	1	1	1	1	1	1	1