

CASTORS KEY



Wheel diameter



External dimension mounting plate



Mounting dimension



Hole diameter



Hole fitting size



Offset dimension



Total height

WHEELS KEY



Tread width



Hub width



Load capacity



Bushing diameter



Bolt size



INDUSTRIAL CASTORS



270 SERIES

Anti-corrosion wheel



Rim: Polypropylene
Tread: Thermoplastic Rubber

Bearing: Plain or Ball Bearing
Load Capacity: 50kg - 100kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
270R50P40	50	60 x 60	48/38 x 48/38	6	30	69	50
270R75P40	75	60 x 60	48/38 x 48/38	6	25	100	75
270R100P60	100	77 x 67	61/56 x 51/46	8	40	135	80
270R125P60	125	77 x 67	61/56 x 51/46	8	45	160	100

278R50P40	50	60 x 60	48/38 x 48/38	6	.	69	50
278R75P40	75	60 x 60	48/38 x 48/38	6	.	100	75
278R100P60	100	77 x 67	61/56 x 51/46	8	.	135	80
278R125P60	125	77 x 67	61/56 x 51/46	8	.	160	100

277R50P40	50	60 x 60	48/38 x 48/38	6	30	69	50
277R75P40	75	60 x 60	48/38 x 48/38	6	25	100	75
277R100P60	100	77 x 67	61/56 x 51/46	8	40	135	80
277R125P60	125	77 x 67	61/56 x 51/46	8	45	160	100

Product Code	 mm	 mm	 mm	 mm	 kg
270R50P30	50	11	30	69	50
270R75P30	75	11	30	100	75
270R100P30	100	13	40	135	80
270R125P30	125	13	45	160	100

277R50P30	50	11	30	69	50
277R75P30	75	11	30	100	75
277R100P30	100	13	40	135	80
277R125P30	125	13	45	160	100

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
PJO050	50	19	21	6	M6	50
PJO075	75	25	30	6	M6	75
PJR100	100	30	35	8	M8	80
PJR125	125	30	35	8	M8	100

INDUSTRIAL CASTORS



VRB SERIES Premium Vulcanised Rubber



Rim: Polyamide
Tread: Grey elastic rubber

Bearing: Ball Bearing
Load Capacity: 200kg - 350kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
380VRB100P62	100	105 x 80	80/77 x 60	9	40	128	200
380VRB125P62	125	105 x 80	80/77 x 60	9	40	255	220
380VRB160P63	160	135 x 110	105 x 84/76	11	55	195	300
380VRB200P63	200	135 x 110	105 x 84/76	11	55	235	350

378VRB100P62	100	105 x 80	80/77 x 60	9	.	128	200
378VRB125P62	125	105 x 80	80/77 x 60	9	.	255	220
378VRB160P63	160	135 x 110	105 x 84/76	11	.	195	300
378VRB200P63	200	135 x 110	105 x 84/76	11	.	235	350

377VRB100P62	100	105 x 80	80/77 x 60	9	40	128	200
377VRB125P62	125	105 x 80	80/77 x 60	9	40	255	220
377VRB160P63	160	135 x 110	105 x 84/76	11	55	195	300
377VRB200P63	200	135 x 110	105 x 84/76	11	55	235	350

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
VRB100	100	35	40	8	M8	200
VRB125	125	38	52	10	M10	220
VRB160	150	46	59	12	M12	300
VRB200	200	46	59	12	M12	350

EXPANSION PLUGS



Shape: Round or Square

Product Code	 mm	 - tube	 - tube	Allenkey Size
R07 - 19/20	19 - 21			M8
R07 - 21/24	21 - 24			M8
R07 - 24/27	24 - 27			M8
R47 - 21/24	21 - 24			M8
R47 - 24/27	24 - 27			M8
R47 - 27/30	27 - 30			M8

INDUSTRIAL CASTORS



22 SER SERIES

Elastic rubber tyred wheel



Rim: Polyamide
Tread: Elastic Rubber

Bearing: Ball Bearing
Load Capacity: 90kg - 250kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
322SER	80	104 x 80	76 x 56	8	30	108	90
422SER	100	104 x 80	76 x 56	8	35	128	120
522SER	125	104 x 80	76 x 56	8	40	159	140
622SER	150	138 x 114	105 x 85	10	47	195	200
822SER	200	138 x 114	105 x 85	10	51	240	250

329SER	80	104 x 80	76 x 56	8	.	108	90
429SER	100	104 x 80	76 x 56	8	.	128	120
529SER	125	104 x 80	76 x 56	8	.	159	140
629SER	150	138 x 114	105 x 85	10	.	195	200
829SER	200	138 x 114	105 x 85	10	.	240	250

322SER/BK	80	104 x 80	76 x 56	8	30	108	90
422SER/BK	100	104 x 80	76 x 56	8	35	128	120
522SER/BK	125	104 x 80	76 x 56	8	40	159	140
622SER/BK	150	138 x 114	105 x 85	10	47	195	200
822SER/BK	200	138 x 114	105 x 85	10	51	240	250

Product Code	 mm	 mm	 mm	 mm	 kg
322SER/BH	80	12	30	108	90
422SER/BH	100	12	35	128	120
522SER/BH	125	12	40	159	140

322SER/BH/BK	80	12	30	108	90
422SER/BH/BK	100	12	35	128	120
522SER/BH/BK	125	12	40	159	140

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
SER80	80	30	37	8	M8	90
SER100	100	32	37	8	M8	120
SER125	125	36	48	10	M10	140
SER150	150	47	55	20/25	M12	200
SER200BB	200	50	59	20/25	M12	250

INDUSTRIAL CASTORS



22 NY SERIES

Nylon tyred wheel



Wheel: Nylon

Bearing: Plain Bearing
Load Capacity: 90kg - 250kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
322NY	80	104 x 80	76 x 56	8	30	108	80
422NY	100	104 x 80	76 x 56	8	35	128	100
522NY	125	104 x 80	76 x 56	8	40	159	140
622NY	150	138 x 114	105 x 85	10	47	195	180
822NY	200	138 x 114	105 x 85	10	51	240	250

329NY	80	104 x 80	76 x 56	8	.	108	80
429NY	100	104 x 80	76 x 56	8	.	128	100
529NY	125	104 x 80	76 x 56	8	.	159	140
629NY	150	138 x 114	105 x 85	10	.	195	180
829NY	200	138 x 114	105 x 85	10	.	240	250

322NY/BK	80	104 x 80	76 x 56	8	30	108	80
422NY/BK	100	104 x 80	76 x 56	8	35	128	100
522NY/BK	125	104 x 80	76 x 56	8	40	159	140
622NY/BK	150	138 x 114	105 x 85	10	47	195	180
822NY/BK	200	138 x 114	105 x 85	10	51	240	250

Product Code	 mm	 mm	 mm	 mm	 kg
322NY/BH	80	12	30	108	80
422NY/BH	100	12	35	128	100
522NY/BH	125	12	40	159	140

322NY/BH/BK	80	12	30	108	80
422NY/BH/BK	100	12	35	128	100
522NY/BH/BK	125	12	40	159	140

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
WNY3/C	80	28	36	12	M8	80
WNY4/C	100	30	36	12	M8	100
WNY5/C	125	40	46	15	M10	140
WNY6	150	39	58	19	M20	180
WNY8BB	200	45	53	20/25	M20/M25	250

INDUSTRIAL CASTORS



22 UAR SERIES

Nylon centred and Polyurethane
tyred wheel



Rim: Nylon
Tread: Polyurethane

Bearing: Ball Bearing
Load Capacity: 90kg - 250kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
322UAR	80	104 x 80	76 x 56	8	30	108	90
422UAR	100	104 x 80	76 x 56	8	35	128	120
522UAR	125	104 x 80	76 x 56	8	40	159	140
622UAR	150	138 x 114	105 x 85	10	47	195	200
822UAR	200	138 x 114	105 x 85	10	51	240	250

329UAR	80	104 x 80	76 x 56	8	.	108	90
429UAR	100	104 x 80	76 x 56	8	.	128	120
529UAR	125	104 x 80	76 x 56	8	.	159	140
629UAR	150	138 x 114	105 x 85	10	.	195	200
829UAR	200	138 x 114	105 x 85	10	.	240	250

322UAR/BK	80	104 x 80	76 x 56	8	30	108	90
422UAR/BK	100	104 x 80	76 x 56	8	35	128	120
522UAR/BK	125	104 x 80	76 x 56	8	40	159	140
622UAR/BK	150	138 x 114	105 x 85	10	47	195	200
822UAR/BK	200	138 x 114	105 x 85	10	51	240	250

Product Code	 mm	 mm	 mm	 mm	 kg
322UAR/BH	80	12	30	108	90
422UAR/BH	100	12	35	128	120
522UAR/BH	125	12	40	159	140

322UAR/BH/BK	80	12	30	108	90
422UAR/BH/BK	100	12	35	128	120
522UAR/BH/BK	125	12	40	159	140

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
UAR080	80	30	38	15	M8	90
UAR100	100	30	38	15	M8	120
UAR125	125	31	38	15	M10	140
WPN6	150	43	60	20	M12	200
WPN8	200	45	60	20	M12	250

INDUSTRIAL CASTORS



22 PU SERIES

Polyurethane tyred wheel



Rim: Cast Iron
Tread: Polyurethane
Bearing: Ball Bearing
Load Capacity: 90kg - 250kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
322PU	80	104 x 80	76 x 56	8	38	108	120
422PU	100	104 x 80	80 x 60	8	45	133	250
522PU	125	104 x 80	80 x 60	8	35	159	250
622PU	150	138 x 114	105 x 85	10	55	195	250
822PU	200	138 x 114	105 x 85	10	55	240	250

329PU	80	104 x 80	76 x 56	8	.	108	120
429PU	100	104 x 80	80 x 60	8	.	133	250
529PU	125	104 x 80	80 x 60	8	.	159	250
629PU	150	138 x 114	105 x 85	10	.	195	250
829PU	200	138 x 114	105 x 85	10	.	240	250

322PU/BK	80	104 x 80	76 x 56	8	38	108	90
422PU/BK	100	104 x 80	80 x 60	8	45	133	120
522PU/BK	125	104 x 80	80 x 60	8	35	159	140
622PU/BK	150	138 x 114	105 x 85	10	55	195	200
822PU/BK	200	138 x 114	105 x 85	10	55	240	250

Product Code	 mm	 mm	 mm	 mm	 kg
322PU/BH	80	12	30	108	90
422PU/BH	100	12	35	128	120
522PU/BH	125	12	40	159	140

322PU/BH/BK	80	12	30	108	90
422PU/BH/BK	100	12	35	128	120
522PU/BH/BK	125	12	40	159	140

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
PU080	80	30	35	10	M8	120
PU100	100	30	37	10	M8	250
PU125	125	40	41	15	M10	250
WPU150	150	46	59	20	M12	250
WPU200	200	46	59	20	M12	250

INDUSTRIAL CASTORS



22 CW SERIES

Cast Iron wheel



Wheel: Cast Iron

Bearing: Plain Bearing
Load Capacity: 120kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
422CW	100	104 x 80	76 x 56	8	35	128	120

429CW	100	104 x 80	76 x 56	8	.	128	120
-------	-----	----------	---------	---	---	-----	-----

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
WCW0312P12	75	28	36	12	M8	120
WCW0412P12	100	32	48	15	M10	200

61 & 88 CW SERIES

Cast Iron wheel



Wheel: Cast Iron

Bearing: Plain Bearing
Load Capacity: 120kg - 200kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
361CW	75	104 x 80	82 x 60	8	20	108	120
461CW	100	128 x 102	103 x 76	8/10	20	128	200

388CW	75	104 x 80	82 x 60	8	.	108	120
488CW	100	120 x 80	100 x 48	8/10	.	128	200

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
WCW0312P12	75	32	40	10	M10	120
WCW0412P12	100	32	48	15	M10	200

INDUSTRIAL CASTORS



61 & 88 NY SERIES

Nylon wheel



Wheel: Nylon

Bearing: Plain Bearing
Load Capacity: 50kg - 200kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
GN32	30	38 x 32	30 x 24	4	15	40	15
GN38	38	46 x 38	34 x 30	5	20	50	20
962NY	50	64 x 48	54 x 26	6	25	64	50
261NY	65	95 x 70	75 x 45	8	20	85	75
361NY	75	104 x 80	82 x 60	8	20	95	125
461NY	100	120 x 80	100 x 48	10	20	125	200
288NY	65	112 x 58	89 x 26	8	.	85	75
388NY	75	104 x 80	82 x 60	8	.	95	125
488NY	100	128 x 102	103 x 76	10	.	125	200

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
WNY20	50	23	26	6	M6	50
WNY25	65	28	34	8	M8	75
WNY3	75	31	38	8	M8	125
WNY4	100	30	47	15	M10	200

61 & 88 PU SERIES

Polyurethane tyred wheel




Rim: Cast Iron
Tread: Polyurethane

Bearing: Ball Bearing
Load Capacity: 125kg - 200kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
361PUR	75	104 x 80	82 x 60	8	15	95	125
461PUR	100	128 x 102	103 x 76	10	20	125	200
388PUR	80	104 x 80	82 x 60	8	.	95	125
488PUR	100	120 x 80	100 x 48	10	.	125	200

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
PUR080	80	30	40	8	M8	125
PUR100	100	30	40	8	M8	200

STAINLESS STEEL CASTORS



STAINLESS STEEL SERIES

Nylon tyred wheel



Wheel: Nylon
Bracket: Stainless Steel

Bearing: Plain Bearing
Load Capacity: 125kg - 180kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
--------------	--	--	---	--	--	--	--

322NY-SS	80	104 x 80	76 x 56	8	40	108	125
422NY-SS	100	104 x 80	76 x 56	8	40	128	180



329NY-SS	80	104 x 80	76 x 56	8	.	108	125
429NY-SS	100	104 x 80	76 x 56	8	.	128	180



322NY-BK-SS	80	104 x 80	76 x 56	8	40	108	125
422NY-BK-SS	100	104 x 80	76 x 56	8	4	128	180



Product Code	 mm	 mm	 mm	 mm	 kg
--------------	--	--	--	--	--

322NY-SS/BH	80	12	40	108	125
422NY-SS/BH	100	12	40	128	180



322NY-SS/BH/BK	80	12	40	108	125
422NY-SS/BH/BK	100	12	40	128	180



Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
--------------	--	--	--	--	---	--

WNY3	80	28	36	12	M12	125
WNY4	100	30	47	15	M15	180

INDUSTRIAL CASTORS



TS & TF SERIES

Heavy duty Castor with
electroplated steel construction



Rim: Cast Iron
Tread: Polyurethane

Bearing: Ball Bearing
Load Capacity: 250kg - 500kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
TS4PUR	100	115 x 100	85 x 72	10	35	143	250
TS5PUR	125	115 x 100	85 x 72	10	39	168	300
TS6PUR	150	115 x 100	85 x 72	10	45	195	400
TS8PUR	200	115 x 100	85 x 72	10	56	240	500
TF4PUR	100	115 x 100	85 x 72	10	.	143	250
TF5PUR	125	115 x 100	85 x 72	10	.	168	300
TF6PUR	150	115 x 100	85 x 72	10	.	195	400
TF8PUR	200	115 x 100	85 x 72	10	.	240	500
TS4PUR/BK	100	115 x 100	85 x 72	10	35	143	250
TS5PUR/BK	125	115 x 100	85 x 72	10	39	168	300
TS6PUR/BK	150	115 x 100	85 x 72	10	45	195	400
TS8PUR/BK	200	115 x 100	85 x 72	10	56	240	500

TH & THR SERIES MEDIUM DUTY

Polyurethane tyred wheel



Rim: Cast Iron
Tread: Polyurethane

Bearing: Ball Bearing
Load Capacity: 350kg - 800kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
TH4PUR	100	155 x 100	116 x 65	13	40	154	300
TH5PUR	125	155 x 100	116 x 65	13	46	185	350
TH6PUR	150	155 x 100	116 x 65	13	46	206	550
TH8PUR	200	155 x 100	116 x 65	13	51	256	750
TH10PUR	250	155 x 100	116 x 65	13	67	307	800
THR4PUR	100	155 x 100	116 x 65	13	.	154	300
THR5PUR	125	155 x 100	116 x 65	13	.	185	350
THR6PUR	150	155 x 100	116 x 65	13	.	206	550
THR8PUR	200	155 x 100	116 x 65	13	.	256	750
THR10PUR	250	155 x 100	116 x 65	13	.	307	800
TH4PUR/BK	100	155 x 100	116 x 65	13	40	154	300
TH5PUR/BK	125	155 x 100	116 x 65	13	46	185	350
TH6PUR/BK	150	155 x 100	116 x 65	13	46	206	550
TH8PUR/BK	200	155 x 100	116 x 65	13	51	256	750
TH10PUR/BK	250	155 x 100	116 x 65	13	67	307	800

INDUSTRIAL CASTORS



TH & THR SERIES HEAVY DUTY

Polyurethane tyred wheel



Rim: Cast Iron
Tread: Polyurethane

Bearing: Ball Bearing
Load Capacity: 350kg - 1000kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
TH4PUR	100	155 x 100	116 x 65	13	40	154	350
TH5PUR	125	155 x 100	116 x 65	13	46	185	400
TH6PUR	150	155 x 100	116 x 65	13	46	206	700
TH8PUR	200	155 x 100	116 x 65	13	51	256	950
TH10PUR	250	155 x 100	116 x 65	13	67	307	1000
TH12PUR	300	155 x 100	116 x 65	13	96	356	1000
THR4PUR	100	155 x 100	116 x 65	13	.	154	350
THR5PUR	125	155 x 100	116 x 65	13	.	185	400
THR6PUR	150	155 x 100	116 x 65	13	.	206	700
THR8PUR	200	155 x 100	116 x 65	13	.	256	950
THR10PUR	250	155 x 100	116 x 65	13	.	307	1000
THR12PUR	300	155 x 100	116 x 65	13	.	356	1000
TH4PUR/BK	100	155 x 100	116 x 65	13	40	154	350
TH5PUR/BK	125	155 x 100	116 x 65	13	46	185	400
TH6PUR/BK	150	155 x 100	116 x 65	13	46	206	700
TH8PUR/BK	200	155 x 100	116 x 65	13	51	256	950
TH10PUR/BK	250	155 x 100	116 x 65	13	67	307	1000
TH12PUR/BK	300	155 x 100	116 x 65	13	96	356	1000

TH & THR SERIES HEAVY DUTY

Cast Iron wheel



Wheel: Cast Iron

Bearing: Ball Bearing
Load Capacity: 500kg - 1000kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
TH4CW	100	155 x 100	116 x 65	13	40	154	500
TH5CW	125	155 x 100	116 x 65	13	46	185	600
TH6CW	150	155 x 100	116 x 65	13	46	206	850
TH8CW	200	155 x 100	116 x 65	13	51	256	900
TH10CW	250	155 x 100	116 x 65	13	67	307	950
TH12CW	300	155 x 100	116 x 65	13	96	356	1000
THR4CW	100	155 x 100	116 x 65	13	.	154	500
THR5CW	125	155 x 100	116 x 65	13	.	185	600
THR6CW	150	155 x 100	116 x 65	13	.	206	850
THR8CW	200	155 x 100	116 x 65	13	.	256	900
THR10CW	250	155 x 100	116 x 65	13	.	307	950
THR12CW	300	155 x 100	116 x 65	13	.	356	1000

INDUSTRIAL CASTORS



STC & FTC SERIES MEDIUM DUTY

Polyurethane tyred wheel



Rim: Cast Iron
Tread: Polyurethane

Bearing: Ball Bearing
Load Capacity: 1300kg - 2500kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
STC200x75PUB - M	200	165 x 130	127 x 89	16.5	50	266	1300
STC250x75PUB - M	250	165 x 130	127 x 89	16.5	68	311	1800
STC300x75PUB - M	300	165 x 130	127 x 89	16.5	94	363	1800

FTC200x75PUB - M	200	165 x 130	127 x 89	16.5	.	266	1300
FTC250x75PUB - M	250	165 x 130	127 x 89	16.5	.	311	1800
FTC300x75PUB - M	300	165 x 130	127 x 89	16.5	.	363	1800

STC & FTC SERIES HEAVY DUTY

Polyurethane tyred wheel



Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
STC200x75PUB - H	200	190 x 150	150 x 110	18.5	60	266	1450
STC250x75PUB - H	250	190 x 150	150 x 110	18.5	66	311	1800
STC300x75PUB - H	300	190 x 150	150 x 110	18.5	88	363	2200
STC400x75PUB - H	400	190 x 150	150 x 110	18.5	108	480	2500

FTC200x75PUB - H	200	190 x 150	150 x 110	18.5	.	266	1450
FTC250x75PUB - H	250	190 x 150	150 x 110	18.5	.	311	1800
FTC300x75PUB - H	300	190 x 150	150 x 110	18.5	.	363	2200
FTC400x75PUB - H	400	190 x 150	150 x 110	18.5	.	480	2500

STC & FTC SERIES EXTRA HEAVY DUTY

Polyurethane tyred wheel



Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
STC250x75PUB - EH	250	240 x 180	197 x 102	18.5	66	330	1800
STC300x75PUB - EH	300	240 x 180	197 x 102	18.5	88	380	2200
STC400x75PUB - EH	400	240 x 180	197 x 102	18.5	108	538	2500

FTC250x75PUB - EH	250	240 x 180	197 x 102	18.5	.	330	1800
FTC300x75PUB - EH	300	240 x 180	197 x 102	18.5	.	380	2200
FTC400x75PUB - EH	400	240 x 180	197 x 102	18.5	.	538	2500

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg Med	 kg Heavy	 kg X-Heavy
WPU083B25	200	75	85	25	M16	1300	1450	.
WPU103B25	250	75	85	25	M16	1800	1800	1800
WPU123B25	300	75	85	25	M16	1800	2200	2200
WPU164B25	400	75	85	25/30	M16	.	2500	2500
WPU164B25	400	100	105	25/30	M16	.	.	2500

SCAFFOLDING CASTORS



SCAFFOLDING NY SERIES

Nylon wheel



Wheel: Nylon

Bearing: Roller Bearing
Load Capacity: 200kg - 350kg

Product Code	 mm	 mm	 mm	 mm	 kg
FG44NY/32	100	100	32	130	200
FG56NY/35/C	150	120	35	200	300
FG58NY/38/C	200	120	38	245	350

SCAFFOLDING PU SERIES

Polyurethane tyred wheel



Rim: Cast Iron
Tread: Polyurethane

Bearing: Roller Bearing
Load Capacity: 350kg - 400kg

Product Code	 mm	 mm	 mm	 mm	 kg
FG56PU/35/C	150	120	35	200	350
FG56PU/38/C	150	120	38	200	350
FG58PU/35/C	200	120	35	245	400
FG58PU/38/C	200	120	38	245	400

SCAFFOLDING PU PLATE SERIES

Polyurethane tyred wheel



Rim: Cast Iron
Tread: Polyurethane

Bearing: Roller Bearing
Load Capacity: 400kg

Product Code	 mm	 mm	 mm	 mm	 kg
FG58PU/PLATE	200	140	110	245	400

SCAFFOLDING PU WITH JACK

Polyurethane tyred wheel



Rim: Cast Iron
Tread: Polyurethane

Bearing: Roller Bearing
Load Capacity: 400kg

Product Code	 mm	 mm	 mm	 mm	 kg
FG58PU/JACK	200	120	35/38	245	400

INDUSTRIAL CASTORS



PNEUMATIC SERIES

Ideal for rough terrain



Rim: Steel
Tread: Rubber

Bearing: Ball Bearing
Load Capacity: 80kg - 100kg

Product Code	 mm	 mm	 mm	 mm	 mm	 kg
TS8PNU/C	220	115 x 100	85 x 72	10	260	80
TS10PNU/C	260	115 x 100	85 x 27	10	300	100

Product Code	 mm	 mm	 mm	 mm	 mm	 kg
TF8PNU/C	220	115 x 100	85 x 72	10	260	80
TF10PNU/C	260	115 x 100	85 x 72	10	300	100

Product Code	 mm	 mm	 mm	 mm	 Ø	 kg
WSP082B	220	60	95	13/16	M12	80
WSP1034B	260	80	100	16/25	M12	100

PNEUMATIC HEAVY DUTY SERIES

Ideal for rough terrain



Rim: Steel
Tread: Rubber

Bearing: Ball Bearing
Load Capacity: 80kg - 100kg

Product Code	 mm	 mm	 mm	 mm	 mm	 kg
TH8PNU/C	220	115 x 100	85 x 72	10	260	80
TH10PNU/C	260	115 x 100	85 x 27	10	300	100

Product Code	 mm	 mm	 mm	 mm	 mm	 kg
THF8PNU/C	220	115 x 100	85 x 72	10	260	80
THF10PNU/C	260	115 x 100	85 x 72	10	300	100

FURNITURE CASTORS

Twin wheel, hooded nylon castor



Wheel: Nylon

Bearing: Ball Bearing
Load Capacity: 50kg - 60kg

Product Code	 mm	 mm	 mm	 mm	 mm	 kg
CM5008BL	50	32 x 8	.	8	.	50
CM5010BL	50	38 x 10	.	10	.	60
CM5008BB	50	38 x 10	.	8	.	60
CM5010BB	50	38 x 10	.	10	.	60

INDUSTRIAL CASTORS



BOLTSTEM CASTOR

Nylon centre with
Rubber tyred wheel



Rim: Nylon
Tread: Rubber

Bearing: Plain Bearing
Load Capacity: 40kg

Product Code	 mm	 mm	 mm	 mm	 mm	 kg
GR75BS	75	35	11	28	135	40

FOOTMASTER

Leveling & shock-absorbing



Rim: Steel
Tread: Nylon

Bearing: Plain Bearing
Load Capacity: 50kg - 750kg

Product Code	 mm	 mm	 mm	 mm	 mm	 mm	 kg
footmaster-40mm	40	55 x 55	42 x 42	7.2	30.5	72	50
footmaster-50mm	50	75 x 75	57 x 57	7.5	38	85.7	250
footmaster-65mm	62	90 x 90	70 x 70	8.8	44	107	500
footmaster-75mm	75	95 x 95	70 x 70	11	53	119	750

GATE KITS

Wheels for sliding gates



Wheel: Mild steel

Bearing: Ball Bearing
Load Capacity: 500kg - 1200kg

Product Code	 mm	 mm	 mm	 kg
GKIT40	43	50 x 45	73	500
GKIT60	48	50 x 45	76	700
GKIT80	68	65 x 45	90	800
GKIT100	100	130 x 50	111	1200

HAMMER / TRUCK LOCK SERIES



Material: Steel

Load Capacity: 200kg - 300kg

Product Code	 mm	 mm	 mm	 mm	 kg
HL4	120 x 120	85/100 x 85/100	10	130 - 150	200
HL5	120 x 120	85/100 x 85/100	10	160 - 175	230
HL6	120 x 120	85/100 x 85/100	10	170 - 210	280
HL8	120 x 120	85/100 x 85/100	10	210 - 245	300