

The ANR/TNR range has a wide variety of pokers and transmissions, with various couplings.

## TECHNICAL DATA TNR TRANSMISSIONS

MODEL	LENGTH (m)	WEIGHT (Kg)
TNR6-25	6	8
TNR6-38	6	15.8
TNR6-48	6	15.8
TNR6-58	6	15.8
TNR6-70	6	15.8

\*Other lengths available upon request



- › High quality transmission.
- › Extra protected Transmission where the transmission attaches to the poker.  
(For 48, 58 and 70mm models)
- › For different types of pins, please consult.
- › Axis rotation frequency: 3.000 r.p.m. Poker vibration frequency: 12.000 v.p.m.
- › Transmission diameter: 26mm for ANR25 poker and 36mm for the others (ANR 38-70).

## TECHNICAL DATA ANR POKERS

MODEL	DIAMETER (mm)	LENGTH (mm)	WEIGHT (Kg)	SPEED (r.p.m)	PERFORMANCE (m³/h)	TRANSMISSION
ANR25	25	350	1.2	16,000	10	TNR4-25/TNR6-25
ANR38	38	375	2.5	12,000	15	TNR4-38/TNR6-38
ANR48	48	445	4.3	12,000	25	TNR4-48/TNR6-48
ANR58	58	450	6.4	12,000	30	TNR4-58/TNR6-58
ANR70	70	510	7.5	12,000	35	TNR4-70/TNR6-70


# ANR/TNR

## PENDULUM POKERS AND TRANSMISSIONS

PETROL/  
DIESEL/  
ELECTRIC


### + Adaptability

The TNR/ANR range adapts to all types of works, thanks to its indistinct operation with electric, petrol or diesel motors.



### + Versatility

Wide range of diameters and couplings adapt to all types of users.



### + Resistance

The greatest stress area is rubber reinforced. Robust mechanical system.