

The DEEP range offers the user manageable, reliable, and easily transportable tramping rammers.




DEEP

TRAMPING RAMMERS



+ Air filter

DEEP rammers have a 3-stage filter that progressively retains particles according to their size.



+ Noise reduction

The fuel tank, located on the handlebar, serves as a barrier, such as acoustic shielding, to reduce the noise that reaches the user.



+ Economic maintenance

Designed for low maintenance cost with cost-controlled wear items.



+ Comfortable

Compensated and balanced jump for a more comfortable use of the machine by the user.



- » The DEEP rammers range offers different models between 65 and 80kg.
- » Different diesel and petrol engines.
- » Dimensions : 770x398x1038 mm.
- » Foot dimensions: 332x280 mm.
- » Number of hits per minute: 650 v.p.m.
- » Optional air filter saturation sensor.
- » Tachometer with optional operating hours and engine revolutions indicator.
- » Large 3-stage air filter.

TECHNICAL DATA

MODEL	WEIGHT WITHOUT FUEL (Kg)	ELEVATION (mm)	IMPACT FORCE (Kg)	ENGINE	SPEED (r.p.m.)	POWER (cv)	PERFORMANCE (m²)	FUEL
PH 70E	73	70	1,540	HONDA GXR120RT KR EE	3,600	4	210	Petrol
PH 70LC	74	70	1,540	ENAR G165F 4 CV	3,600	4	210	Petrol
PH 80YD	81	70	1,510	YANMAR L 48 AE	3,600	4	205	Diesel